GreenStar[™] 3 2630 Display

Software Versions

The items in this chart are included in this software bundle. Bold items have changed from previous releases with either new feature enhancements or resolved items. Please contact your John Deere dealer to update controllers not included with this software bundle.

Version #	Description
3.36.1073	GreenStar™ 2630 Display
2.8.1033	GreenStar™ 2100/2600 Display
2.15.1096	GreenStar™ 1800 Display
GSD 1.97 B	Original GreenStar™ Display
GR6 4.30 F	StarFire™ 6000 Receiver
ITC 2.70 A	StarFire™ 3000 Receiver
ITC 3.73 H	StarFire™ iTC Receiver
LCR 1.10 C	StarFire™ 300 Receiver
SF 7.70 B	StarFire™ Gen II Receiver
1.10A	Machine Communication Radio
TCM 1.09 A	TCM
2.71 Z	Application Controller 1100 (iGrade™, Active Implement Guidance,
	Distance Trip) (S.N. PCXL01B100000 -)
1.51 Y	Application Controller 1120 (Yield Documentation Specialty Crop,
	Mobile Weather, Harvest Identification, Cotton) (S.N. PCXL02B100000 -)
3.11 K	Application Controller 1100 (iGrade [™] , Active Implement Guidance,
	Distance Trip) (S.N. PCXL01C201000 -)
3.11 K	Application Controller 1120 (Yield Documentation Specialty Crop,
	Mobile Weather, Harvest Identification, Cotton) (S.N. PCXL02C201000 -)
ATU 1.13 A	AutoTrac™ Universal 100
ATU 2.30 A	AutoTrac™ Universal 200
ATU 3.23 H	AutoTrac™ Universal 300
RG2 2.04 B	AutoTrac™ RowSense™ – Universal
CAT 1.11 B	AutoTrac [™] Controller (Deere)
ATC 3.23 H	AutoTrac™ Controller 300
GRC 3.70 K	GreenStar™ Rate Controller
GDC 2.11 A*	GreenStar™ Rate Controller Dry
VGC 4.01 V	AutoTrac™ Vision Guidance
HMCT 1.20 A	Harvest Monitor™ Cotton SCM
CMFS 2.07 C	Cotton Mass Flow Sensor CMFS
SMON 1.73 A	Original Harvest Monitor™ SPFH
HMON 1.20 C	Harvest Monitor™ Combine with In-Tank Moisture
MST 7.01 B	Harvest Monitor™ Elevator Mount Moisture Board
AC2.11	Original Air Cart
SMVR 1.01 M	SeedStar™ Gen II

Important Notes:

- Installation time will vary depending on the amount of existing data and the software version currently on the display. On average, total install time is 10-15 minutes.
- It is recommended to back up display data, prior to updating any Software as a precaution, to protect your information.
- It is suggested to erase all data from your GreenStar[™] 3 2630 Display before loading new Setup Data, in an effort to remove unnecessary and potentially corrupt files that may hinder display performance.
- To ensure complete and proper functionality, the most current version of GreenStar[™] Display and Operations Center, Apex[™], or preferred partner desktop software should be used.

Compatibility:

- For John Deere Machine Sync functionality, GreenStar[™] 3 2630 Displays must operate with matching software versions. (18-1 recommended).
- For John Deere Machine Sync coverage map sharing, shared coverage maps will not persist after updating displays from SU15-2 to any newer version. Perform software update at the conclusion of field operations to ensure no coverage maps are lost.
- Coverage maps will not persist if GreenStar[™] 3 2630 Display software is backdated from 18-1 to SU15-2 or older software version.
- ISOBUS AEF Certification functionality is only approved for 30 Series and newer tractors.
- ISOBUS AEF Certification functionality will disable the use of the virtual Original GreenStar™ Monitor mode within the GreenStar™ 3 2630 Display and controllers that are designed for use with the Original GreenStar™ Monitor mode.
- Turn on the Original GreenStar[™] Monitor emulator when reprogramming controllers through the display. This is required for most legacy controllers.
- Generation 4 CommandCenter[™] setup profiles will not directly import into the GreenStar[™] 3 2630 Display. In order to import Gen4 CommandCenter[™] profiles, first export data from the GreenStar[™] 3 2630 Display with the profile name "JD4600". Next, using the same USB, export all data from the Gen4 CommandCenter[™]. All data will be merged into the JD4600 profile and then can be imported into the GreenStar[™] 3 2630 Display.
- Software Version (18-1) is backwards compatible on all previous GreenStar[™] 3 2630 Display hardware revisions. GreenStar[™] 3 2630 Display software (15-2 and earlier) is not compatible with new GreenStar[™] 3 2630 Display hardware revision H and later. GreenStar[™] 3 2630 Display software (16-1 and earlier) is not compatible with new GreenStar[™] 3 2630 Display hardware revision J and later. Hardware revision letter is found in the 7th digit of the display's serial number.
- Software version 18-1 is backward compatible with AYM controller software older than v83.11.
- All data created with 18-1 software will not be backwards compatible. Data created with software versions 17-1 and older will need to be cleared off display and a new setup file will need to be imported.
- For full Coverage Map Sharing (CMS) functionality, GreenStar[™] 3 2630 Displays must operate on 18-1 software.

StarFire[™] 6000 & StarFire[™] 6000 Integrated Receiver

New Features:

<u>StarFire™ 6000 Integrated Receiver Software-</u> The 20-1 software release is the first software release compatible for use with the StarFire™ 6000 Integrated Receiver.

See operator's manual for further information about the StarFire™ 6000 Integrated Receiver software functions.

AutoTrac[™] Controller 300

Important Notes:

The John Deere AutoTrac[™] Controller 300 Kit is for customers who want to equip their fleet with an integrated John Deere Guidance System. This kit is designed for many brands of machines.

Compatibility:

The AutoTrac[™] Controller 300 is compatible with all tractors EXCEPT:

- Sound-Gard[™] body tractors (and others with Gerotor steering valve)
- Machines with active wheel angle sensor to steering wheel movement logic
- Windrowers
- Two-Track machines
- Electric power steering (Gator[™] utility vehicles)
- Steer by wire steering systems
- Dynamic load sense circuits
- Reactive Steering machines
- Tractors brands other than Deere unless connected to power beyond connections
- MY16-MY18 Case IH Steiger® tractors Please use the AutoTrac™ Controller 250 Steering Kit for these tractors.

Release Notice

These are software release notes for GreenStar[™] 3 Displays and related products. Release Notes can be found on <u>www.stellarsupport.com</u>. Note: Your use of the software is governed by the End User License Agreement included with the software.

Copyright © 1996-2020 Deere & Company